

Decor Exterior Plastic Emulsion

Jenson & Nicholson Decor Exterior Plastic Emulsion, a water based acrylic paint is suitable for application on prepared exterior wall surfaces. Providing excellent coverage and durability, the product also protects against algae formation in dry to medium humid climatic conditions.

PRODUCT BENEFITS



- Excellent Hiding & Coverage
- Good Exterior Durability in economical range
- Good Anti-Algal & Anti-Fungal Characteristics
- Good Flow & Ease-of-application
- Value for Money



PRODUCT FEATURES

AVAILABLE PACK SIZES



1 litre

4 litres

10 litres

20 litres

COLOURS



Available in more than 1600+ shades as per the J&N Fan Deck

COVERAGE



55 - 65* sq ft / litre for two coats finish under normal conditions

*Actual coverage may vary due to factors such as method and condition of application, surface roughness and porosity and weather conditions.

RECOMMENDED USE

Jenson & Nicholson Decor Exterior Plastic Emulsion is perfect for painting exterior walls, cement plasters, exterior ceilings, asbestos sheets, concrete, etc.

*Not be applied on surfaces/substrates with continuous seepage or dampness



SURFACE DRYING TIME



Technical Data:

Colour	:	White & Colours
Gloss / Sheen	:	Matt
Recommended Dilution	:	Brush / Spray / Roller up to 70% by volume with water, depending on the application consistency required
Surface Dry time	:	30 minutes* (25°C / 50% RH)
Over coating period	:	4 - 5 hrs* (25°C / 50% RH)
Stability of thinned paint	:	Use within 24 hours

*Recoat and drying period may vary under different conditions



HOW TO PREPARE (SURFACE / WALL)

- Ensure that the surface is free from dust, dirt, chalking, oil, grease, loosely bound particles or any other contamination.
- Ensure removal of Algae and Fungal growth, if any using wire brushing and bio wash solution.
- Sand the glossy surface using Emery Paper 180, as it results in a roughened surface for good adhesion of the primer to the surface.



New concrete, masonry or plaster: Allow the newly constructed cement surface to cure for minimum of 30 days, prior to application of J&N Acrylic Base Water Thinnable Exterior Cement Primer. Ensure that the wall to be painted is completely dry and free from any cement residue.

How to apply ?

- Apply one coat of J&N Acrylic Base Water Thinnable Exterior Cement Primer at the recommended dilution level, using standard brush or roller. Let it dry for minimum 4-6 hours. Apply one more coat of the Primer, if required.
- Dilute Jenson & Nicholson Decor Exterior Plastic Emulsion as per the recommended ratio and apply two coats of the product using standard brush or roller. Allow it to dry for 4-5 hrs and apply further coats, if needed.

Application precautions:

- Do not apply when the ambient temperature drops to levels below 10° C or rises above 45° C within 4 hours of application.
- Do not over thin the product above the suggested dilution levels.
- Do not apply the diluted material after storing for over 24hrs.
- It is advised not to apply the product on surfaces/substrates with continuous seepage or dampness.
- Stir the paint properly before use.
- Seal the container when not in use.

Post Application care:

Ensure proper washing and cleaning of all dust, Algal and Fungal growth at regular intervals of 5-6 months, for longer durability and better retention of aesthetics.

For product related queries, feedback and quality complaints, Please contact:

Customer care: +91 8300 03 05 05

E-mail: ccc@jnpl.in, Visit us: www.jnpl.in

Regd. Office: Jenson & Nicholson Paints Private Ltd.

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600 098. Tamil Nadu, INDIA.

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.

Storage and Transportation:

- Store the containers at constant temperatures, away from direct sunlight / elevated temperature.
- Keep the product in frost-free environment.
- Store the containers in upright position to avoid leakage or damage.
- Do not pour the waste paint in drains or other water sources.

Shelf Life:

2 years from the date of manufacture in the original tightly closed containers, stored away from direct sunlight and excessive heat.

Packaging:

White: 1L, 4L, 10L and 20L packs.

Bases: 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr packs. (Colorants added extra)

What are the precautions ?

- Keep containers upright, tightly closed in a cool, dry, well ventilated place.
- Ensure opened containers are tightly closed, when not in use.
- Store away from excessive heat, direct sunlight and other flammable materials.
- Highly Flammable product so, store in place away from heat and sparks and No smoking to be allowed near the product.
- Keep out of reach of children and pets.
- Do not store near food, drinks or animal feed.
- Do not mix with incompatible materials.
- Use personal protective equipment like goggles, face masks and gloves.
- Ensure good ventilation during application and drying.
- Do not inhale the vapour or spray.
- In case of contact with eyes or skin, wash immediately using plenty of water. Seek medical advice, if irritation persists.
- In case of ingestion, seek immediate medical attention and do not induce vomiting.
- Do not dispose any spilled or unused paint in drain, water bodies and landfill.
- Dispose spillages or unused paint and containers, through appropriate disposal agency.