

### AEROSOL PAINT

Aerosol is a ready to use spray paint supplied in spray containers



### PRODUCT FEATURES

Product type and colours :

Primer	Red brown
Top coat	White, Matt white, yellow, Gold, Blue, Green, grey, red, red brown, Black and matt black
Base coat	Silver medium and silver coarse
Clear coat	Glossy and matt clear

Spray nozzle : Two, Broad spray and narrow spray



Broad spray



Narrow spray

Drying time (25° C /50%RH) :

- Tack free - 20 mins maximum
- Hard dry - 6 hrs. maximum

### SURFACE PREPARATION & APPLICATION DATA

Ensure removal of all dirt, grease and loosely bond or flaking material from the surface. Any traces of oil or grease should be removed with solvent wiping.

Application Procedure : Shake well before the application, open the outer cap, Choose & fix the nozzle as required. And press the top side of the nozzle to spray towards the target object. While spraying maintain a distance of 20 – 30 cm between target object/substrate and spray nozzle

Packing : 400 ml

**SHEENLAC NOROO Coatings India Private Limited (A Joint Venture of SHEENLAC PAINTS & NOROO COATINGS)**

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600098.

For product related queries, feedback and quality complaints, please contact: +91 8300 03 06 06,

Email: [ccc@sheenlacnoroo.in](mailto:ccc@sheenlacnoroo.in), Visit us: [www.sheenlacnoroo.in](http://www.sheenlacnoroo.in)

## SAFETY FEATURES

- ❖ Refer the MSDS of the product which is available on request.
- ❖ Keep out of reach of children. Use personal protective equipment's like goggles, face masks, gloves.
- ❖ In case of contact with eyes or skin, immediately rinse or wash appropriately using plenty of water and seek medical advice if any sort of irritation persists.
- ❖ Do not inhale the vapour or spray.
- ❖ In case of ingestion seek immediate medical attention.

## STORAGE AND TRANSPORTATION

- ❖ Shake the spray bottle every time before use and close it properly after use
- ❖ Do not store or transport the containers under direct sunlight or at elevated temperatures/ near any fire hazard
- ❖ Store the container in an upright position in order to avoid any leakage or damage.

## SHELF LIFE

12 months from the date of manufacture if stored in the original tightly closed container and stored away from direct sunlight and excessive heat

---

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon the atmospheric condition, application methodologies and substrates. SHEENLAC NOROO Coatings India Private Limited however makes no warranty as to the accuracy or sufficiency of such information

**SHEENLAC NOROO Coatings India Private Limited (A Joint Venture of SHEENLAC PAINTS & NOROO COATINGS)**

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600098.

For product related queries, feedback and quality complaints, please contact: +91 8300 03 06 06,

Email: [ccc@sheenlacnoroo.in](mailto:ccc@sheenlacnoroo.in), Visit us: [www.sheenlacnoroo.in](http://www.sheenlacnoroo.in)