

SHEENIAC

SPECIALITY COATINGS

WATER BASED



WOOD POLISH

PolyUrethane (PU)

Interior Wood Finish



WATER BASED WOOD POLISH

Sheenlac Water base (WB) Interior heavy duty wood polish is an easy-to-use product at an economical cost factor that dries very quickly to a crystal-clear film. It has very low environmental impact during and after application.

It's not just a wax polishing
but by
providing a real coating
which will last for years.

AREA OF USAGE

Ideal for Restoration of polish work on furniture, wood panelling, doors, table tops, wood carvings, etc.



AVAILABLE PACKS



500 ml



1L

PRODUCT BENEFITS

EASY APPLICATION

Product can be applied using ragging with cloth, Brush, Roller or by spray

EXCELLENT COMPATIBILITY

Re-polishing process over previously lamination polished wooden surface like Melamine or PU polish made easy without scrape it out. Yes, WB Wood polish will not built the additional film thickness and can apply directly over any pre-polished surface.

PERFORMANCE

The product has best in Water and Alcohol resistance, no cracking, peel-off on ageing and fade out effects and maintains sheen level for a longer period compared to conventional polish.

MAINTAIN THE COLOR

Unlike conventional Polishes, WB Polish is colourless and will maintain its colour for years. This will keep the original wood colour unchanged on ageing which is highly required for light coloured wood.

ECO FRIENDLY

Non-flammable, no odour, wash tools with water and Child safe during and after application.

SALIENT FEATURES



Interior



Water
resistant



Abrasion
resistant



Heat
resistant



Chemical
resistant



Ultra
hard



Quick
drying



Water
wash-up



16 hours
cure



Food &
child safe

APPLICATION METHOD

RESTORATION OF POLISH WORK

Why we need Restoration?

Wooden furniture and its surface often suffers from a build-up of dirt and grime, with the diminished colour and lustre resulting in a dull appearance. This is due to daily usage which leads to wear and tear. It is very much essential to maintain the shine and lustre and also the natural wood grains by timely renewing or restoring the wood polish. We suggest them to re-polish every 5-6 years. Follow these few simple steps to revive the old wood polish and make it fresh.

- Check the condition of previously applied polish and ensure no visible scratch marks, peel off, cracks and color fade out.
- Clean the surface with mild soap solution followed by a thorough clean with water and allow it to dry.

WB Wood Polish Application procedure

- Dilute the Water based (WB) Wood polish with 30 - 40% potable water.
- Always apply a thin layer using white Acrylic hair brush.
- For a full glossy finish, apply 3 coats of WB Glossy Polish.
- If you prefer Matt finish, 2 coats of WB Matt polish will bring the desired finish.
- Allow 90 mins time interval between each coat.
- Sanding is not required in between the coats; for any dust removal scrub gently using #400 Emery paper.

Dent and Colour correction procedure

- To repair any scratch marks, cracks or patchy color on the substrate, scrub mildly using #320 Emery paper.
- Wipe out the dust and fill the dents, cracks with Sheenlac Water base Paste wood filler.
- Scrub and remove the excess filler after one hour using #320 Emery paper.
- Apply appropriate Sheenlac wood stain color using white cloth to match the substrate color and allow to dry for an hour.
- Follow the WB application procedure as explained above.

On Fresh wood

On bare wood sand with grain using #120 grit and finish with #220 grit emery paper. Wood must be clean, dry and free of grease, oil, dirt, and any contamination. Fill dents, pores with Sheenlac water base Paste wood filler to create a smooth, closed grain surface. To get the desired colour use Solvent or Water base wood stains and allow it to dry for 2 hours.

For Glossy finish

Apply 2 coats of WB matt. polish to fill the micro pores, followed by 3 coats of WB Glossy Polish to get a smooth finish.

Use of 2-3 coats of Sheenlac NC sanding sealer (diluted with NC Thinner @ 1:1 ratio) is also recommended as an alternate method to fill the micro pores, followed by 3 coats of WB Glossy polish.

For Matt Finish

Apply minimum 3 coats of WB Matt Polish over the prepared surface.

TOWARDS DIAMOND JUBILEE YEAR
SINCE 1962

THANK YOU

*Most trusted brand
for Wood coatings*

Sheenlac Paints

124, DEVELOPED PLOTS,
SIDCO INDUSTRIAL ESTATE,
AMBATTUR, CHENNAI - 600 098
Phone: 044 - 4394 9900

Customer Care: +91 83000 30404
Mail: ccc@sheenlac.in

www.sheenlac.com