

ENAMEL THINNER

This is a paint thinner for diluting single pack Enamels and primers. Designed to improve the flow of alkyd and oil based products. It Can also be used as also be used for the degreasing / cleaning of heaving soiled bare metals.



RECOMMENDED USE

Use with Alkyd based Enamel colours, clears, Varnishes, and wood and metal primers as a Thinner and cleaner.

FEATURES & BENEFITS:

- Improves paint consistency.
- Allows paint to acquire optimum film characteristics.
- Fast drying with professional gloss finish.
- Removing wax and grease prior to spraying.

TECHNICAL DATA

Color	:	Clear Transparent
Odour	:	Mild aromatic
Specific gravity	:	~ 0.79 ± 0.02
Flash Point	:	>35° C
Shelf life	:	Best before 12 months in PET bottle.

APPLICATION NOTES

The ratio of thinner to paint should be in accordance with paint manufacturer's guidelines. A general guide is 1 part thinner to 4 parts paint.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin- Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



ENAMEL THINNER (I)

This is a paint thinner for diluting single pack Enamels and primers. Designed to improve the flow of alkyd and oil based products. It Can also be used as also be used for the degreasing / cleaning of heaving soiled bare metals.



RECOMMENDED USE

Use with Alkyd based Enamel colours, clears, Varnishes, and wood and metal primers as a Thinner and cleaner.

FEATURES & BENEFITS:

- Improves paint consistency.
- Allows paint to acquire optimum film characteristics.
- Fast drying with professional gloss finish.
- Removing wax and grease prior to spraying.

TECHNICAL DATA

Color	:	Clear Transparent
Odour	:	Mild aromatic
Specific gravity	:	~ 0.780 ± 0.010
Flash Point	:	>35° C
Shelf life	:	Best before 24 months in Drum.

APPLICATION NOTES

The ratio of thinner to paint should be in accordance with paint manufacturer's guidelines. A general guide is 1 part thinner to 4 parts paint.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin - Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



20 L

NC THINNER D-13 X

PERFORMANCE THINNER.

SHEENLAC NC Thinner D-13 X is a mix of aromatic hydrocarbon, ester, glycol and alcohol. Due to its fast evaporating character, it is suitable for nitrocellulose based undercoats, and primers. Economy variant of NC Thinner for multi-level use.



RECOMMENDED USE

For diluting NC sealer, primer, clear matt and pigmented topcoat. They are also very effective for the thorough cleaning of spray guns and equipment.

FEATURES & BENEFITS:

- Quickly reduces the consistency of the lacquer to the required degree.
- Fast drying and forms a hard film in a shorter period and reduces the risk of imperfections.
- Effective cleaning property makes it a ideal choice for removing stains, paints spills, some inks, waxes, PVC adhesives, tools and hand cleaning.

TECHNICAL DATA

Color	: Clear Transparent
Odour	: Mild aromatic
Specific gravity	: ~ 0.82 ± 0.02
Flash Point	: >10° C
Shelf life	: Best before 6 months in PET bottle

APPLICATION NOTES

While excess usage / over thinning is not advisable in any system, one can add 200% of the concerned Thinner for NC Basecoat ease of application (clear and pigmented), and 100% for NC topcoat range.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin- Wash skin thoroughly with soap and water or approved Industrial cleaner. **DO NOT USE** solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



500ml

1L

3 L


5 L

20 L

NC THINNER D13X (I)

PERFORMANCE THINNER.

SHEENLAC NC Thinner D-13 X(I) is a mix of aromatic hydrocarbon, ester, glycol and alcohol. Due to its fast evaporating character, it is suitable for nitrocellulose based undercoats, and primers. Economy variant of NC Thinner for multi-level use.



RECOMMENDED USE

For diluting NC sealer, primer, clear matt and pigmented topcoat. They are also very effective for the thorough cleaning of spray guns and equipment.

FEATURES & BENEFITS:

- Quickly reduces the consistency of the lacquer to the required degree.
- Fast drying and forms a hard film in a shorter period and reduces the risk of imperfections.
- Effective cleaning property makes it a ideal choice for removing stains, paints spills, some inks, waxes, PVC adhesives, tools and hand cleaning.

TECHNICAL DATA

Color	: Clear Transparent
Odour	: Mild aromatic
Specific gravity	: ~ 0.790 ± 0.010
Flash Point	: >10° C
Shelf life	: Best before 24 months in Drum & barrel

APPLICATION NOTES

While excess usage / over thinning is not advisable in any system, one can add 200% of the concerned Thinner for NC Base coat ease of application (clear and pigmented), and 100% for NC topcoat range.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin - Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



20 L



200 L

POLYURETHANE THINNER D-67

Sheenlac Polyurethane Thinner D-67 is a blend of aromatic hydrocarbon, ester and ketone solvents suitable for dilution of solvent based polyurethane sealer, primer, clear and pigmented topcoat to obtain proper paint consistency for application.



RECOMMENDED USE

Suitable for dilution of all types of solvent based polyurethane sealer, primer, clear and pigmented topcoat. It is also used for cleaning of tools immediately after application of polyurethane paints.

FEATURES & BENEFITS:

- Quickly reduces the consistency of the polyurethane to the required degree.
- Medium Evaporating type makes it suitable to use all Indian climatic conditions.

TECHNICAL DATA

Color	:	Clear Transparent
Odour	:	Mild aromatic
Specific gravity	:	~ 0.88 ± 0.02
Flash Point	:	>25° C
Shelf life	:	Best before 6 months in PET bottle.

APPLICATION NOTES

Recommended up to 50 % by volume according to type of equipment and application method.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin- Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



POLYURETHANE THINNER D-67(IG)

Sheenlac Polyurethane Thinner D-67(IG) is a blend of aromatic hydrocarbon, ester and ketone solvents suitable for dilution of solvent based polyurethane sealer, primer, clear and pigmented topcoat to obtain proper paint consistency for application.



RECOMMENDED USE

Suitable for dilution of all types of solvent based polyurethane sealer, primer, clear and pigmented topcoat. It is also used for cleaning of tools immediately after application of polyurethane paints.

FEATURES & BENEFITS:

- Quickly reduces the consistency of the polyurethane to the required degree.
- Medium Evaporating type makes it suitable to use all Indian climatic conditions.

TECHNICAL DATA

Color	:	Clear Transparent
Odour	:	Mild aromatic
Specific gravity	:	~ 0.88 ± 0.010
Flash Point	:	>25° C
Shelf life :Best before 24months Drum &barrel.		

APPLICATION NOTES

Recommended up to 50 % by volume according to type of equipment and application method.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin- Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



20 L

NC THINNER – SP 58

HIGH PERFORMANCE THINNER.

Premium grade SHEENLAC NC THINNER SP 58 is based on a mixture of esters, glycol, aromatic solvents and ketones, provide a suitable diluent to all nitro products. It is manufactured for reduce lacquers before being utilized in different methods.



RECOMMENDED USE

Wood and Automotive NC Topcoats (clear and Pigmented); Acts as an Anti-blushing agent in high Humid condition. Suitable for Melamine Wood finish.

FEATURES & BENEFITS:

- Quickly reduces the consistency of the lacquer to the required degree.
- Improves film smoothness of lacquers when applied either by spray or dipping thus extending excellent finish.
- Lacquer driers without blushing, resin blush, pin holing and other surface defects.
- No orange peel developed after the evaporation of NC Thinner, and therefore increase the tensile strength of the film along with its gloss.
- NC Thinner has a certain action preventing milky effect of the surface.

TECHNICAL DATA

Color	: Clear Transparent
Odour	: Mild aromatic
Specific gravity	: ~ 0.86 ± 0.02
Flash Point	: >11° C
Shelf life	: Best before 6 months in PET bottle and 1 year in Tin can.

APPLICATION NOTES

While excess usage / over thinning is not advisable in any system, one can add 200% of the concerned Thinner for NC Basecoat ease of application (clear and pigmented), and 100% for NC topcoat range.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin- Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



500ml

1L

3 L

5 L

20 L

NC THINNER - SP 58(I)

HIGH PERFORMANCE THINNER.

Premium grade SHEENLAC NC THINNER SP58(I) is based on a mixture of esters, glycol, aromatic solvents and ketones, provide a suitable diluent to all nitro products. It is manufactured for reduce lacquers before being utilized in different methods.



RECOMMENDED USE

Wood and Automotive NC Topcoats (clear and Pigmented); Acts as an Anti-blushing agent in high Humid condition. Suitable for Melamine Wood finish.

FEATURES & BENEFITS:

- Quickly reduces the consistency of the lacquer to the required degree.
- Improves film smoothness of lacquers when applied either by spray or dipping thus extending excellent finish.
- Lacquer driers without blushing, resin blush, pin holing and other surface defects.
- No orange peel developed after the evaporation of NC Thinner, and therefore increase the tensile strength of the film along with its gloss.
- NC Thinner has a certain action preventing milky effect of the surface.

TECHNICAL DATA

Color	: Clear Transparent
Odour	: Mild aromatic
Specific gravity	: ~ 0.86 ± 0.010
Flash Point	: >11° C
Shelf life	: Best before 24 months in Drum.

APPLICATION NOTES

While excess usage / over thinning is not advisable in any system, one can add 200% of the concerned Thinner for NC Basecoat ease of application (clear and pigmented), and 100% for NC topcoat range.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.
- Contains no added mercury.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin - Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion **Do not induce Vomiting**. Obtain immediate medical attention.

STORAGE & PACKING

To be stored in a cool, dry & well ventilated place away from moisture, heat and direct sunlight.

Packaging



20 L



200 L

NC THINNER G-22/002

PERFORMANCE THINNER.

SHEENLAC NC Thinner G-22/002 is a mix of aromatic hydrocarbon, ester, glycol and alcohol.

Due to its fast evaporating character, it is suitable for nitrocellulose based undercoats, and primers. Economy variant of NC Thinner for multi-level use.

RECOMMENDED USE

For diluting NC sealer, primer, clear matt and pigmented topcoat. They are also very effective for the thorough cleaning of spray guns and equipment.

FEATURES & BENEFITS:

- Quickly reduces the consistency of the lacquer to the required degree.
- Fast drying and forms a hard film in a shorter period and reduces the risk of imperfections.
- Effective cleaning property makes it a ideal choice for removing stains, paints spills, some inks, waxes, PVC adhesives, tools and hand cleaning.

TECHNICAL DATA

Color	: Clear Transparent
Odour	: Mild aromatic
Specific gravity	: ~ 0.790 ± 0.10
Flash Point	: >10° C
Shelf life	: Best before 24 months in Drum and barrel

APPLICATION NOTES

While excess usage / over thinning is not advisable in any system, one can add 200% of the concerned Thinner for NC Base coat ease of application (clear and pigmented), and 100% for NC topcoat range.

HEALTH & SAFETY INSTRUCTIONS

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.
- When applying paint, it is advisable to wear suitable eye protection.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.

SAFETY PRECAUTION:

Eyes - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin- Wash skin thoroughly with soap and water or approved Industrial cleaner. **DO NOT USE solvent or thinners.**

Inhalation - Remove to fresh air, loosen collar and keep patient rested.

Ingestion - In case of accidental ingestion Do not induces Vomiting. Obtain immediate medical attention.

