


JN Classic Emulsion - Exterior

Jenson & Nicholson Classic Emulsion - Exterior is a budget friendly water-based acrylic emulsion is suitable for application on prepared exterior wall surfaces.

PRODUCT BENEFITS

- Good Hiding & coverage
- Good Exterior Durability in economical range
- Good Anti-Algal & Anti-Fungal Characteristics
- Good Flow & Ease-of-application
- Value for Money



PRODUCT FEATURES

AVAILABLE PACK SIZES



COVERAGE



50-60 Sq.ft. / Ltr for 2 coats*

*Actual coverage may vary due to factors such as method and condition of application, surface roughness, porosity and weather conditions.

RECOMMENDED USE

Jenson & Nicholson Classic Emulsion - Exterior is perfect for exterior surfaces like plastered surface, ceilings, asbestos, concrete and hard boards.



SURFACE DRYING TIME



Technical Data:

Colour	:	White
Gloss / Sheen	:	Matt
Recommended Dilution	:	40 to 50% with water, depending on the application consistency required
Surface Dry time	:	30 minutes** (25°C / 50% RH)
Over coating period	:	4 - 5 hrs** (25°C / 50% RH)
Stability of thinned paint	:	Use within 24 hours

**Re-coat and drying period may vary under different conditions



HOW TO PREPARE (SURFACE / WALL)

Surface Preparation:

- Ensure that the surface is free from dust, dirt, grease, loosely bound particles or any flaking material.
- Ensure removal of Algae and Fungal growth, if any, using wire brushing and clean it with water.
- Sand the glossy surface using Emery Paper 180, as it results in a roughened surface for good adhesion of the primer to the surface.



HOW TO APPLY ?

Apply one coat of J&N Universal Primer at the recommended dilution level, using standard brush or roller. Let it dry for minimum 4-6 hours. Apply one more coat of the Primer, if required.

Dilute Jenson & Nicholson Classic Emulsion - Exterior as per the recommended ratio and apply two coats of the product using standard brush or roller. Allow it to dry for 4-5 hrs and apply further coats, if needed.

Application precautions:

- Ensure during application time, the surface temperature and air temperature are not below 10°C or above 45°C.
- Should not over thin the paint above the recommended dilution levels.
- Stir the paint properly before use.
- Seal the container when not in use.
- Do not apply during rains or extreme temperatures
- Avoid mishandling which may lead to puncturing of membrane

Post application care:

For best performance of paint, ensure proper washing of painting surface and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

Storage and Transportation:

- Do not store or transport the containers under direct sunlight / elevated temperatures.
- Store the containers in upright position to avoid leakage or damage.

Shelf Life:

3 years from the date of manufacturing in originally tightly closed containers away from direct sunlight and excessive heat.

Pack Size:

White: 1L, 4L, 10L and 20L packs.

PRECAUTIONS

- Keep containers upright, tightly closed in a cool, dry, well ventilated place.
- Ensure opened containers are tightly closed, when not in use.
- Store away from excessive heat, direct sunlight and other flammable materials.
- Keep out of reach of children and pets.
- Do not store near food, drinks or animal feed.
- Do not mix with incompatible materials.
- Use personal protective equipment like goggles, face masks and gloves.
- Ensure good ventilation during application and drying.
- Do not inhale the vapour or spray.
- In case of contact with eyes or skin, wash immediately using plenty of water. Seek medical advice, if irritation persists.
- In case of ingestion, seek immediate medical attention.
- Do not dispose any spilled or unused paint in drain, water bodies and landfill.
- Dispose spillages or unused paint and containers, through appropriate disposal agency.
- This product does not have any added Lead, Cadmium, Mercury & Chromium.

For product related queries, feedback and quality complaints, Please contact:

Customer care: +91 8300 03 04 04

E-mail: ccc@sheenlac.in,

Visit us: www.jnpl.in

Regd. Office: Jenson & Nicholson Paints Private Ltd.

(A joint venture of Jenson & Nicholson India Ltd and Sheenlac Paints Ltd)

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600 098. Tamil Nadu, INDIA.

TDS / 2022 / Ver.1.0



All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.